

# Suction and delivery ~ Special duty



## SPIRABEL® VENDANGES S.F.

+60  
°C  
-25




✓ fruit juices  
✓ wines

✓ alcohols

### Spiral hose for wine producing applications with up to 50% alcohol content.

Shockproof rigid PVC spiral and flexible transparent PVC wall. Smooth exterior for diameters up to 63mm. Food quality.



- 1 Red spiral in shockproof rigid PVC
- 2 Flexible transparent PVC wall

Marking : SPIRABEL VENDANGES SF Ø inn 2007/19/CE - GARANTI SANS PHTHALATES - QUALITÉ SOUPLE A FROID [batch number]

#### APPLICATIONS

- Wine growing
- Transfer of food liquids

#### SECTORS OF ACTIVITY

- Wine producing
- Food processing

#### ADVANTAGES

With its excellent properties under pressure and during suction, Spirabel Vendanges SF hose is extremely flexible, even at low temperatures, thanks to its specially formulated flexible PVC core. Its smooth interior minimizes flow loss, avoids retention areas and makes rinsing easy. Its outer layer is also smooth to make it easy to tighten the collars and reduce abrasion on the ground. Spirabel Vendanges SF is perfect for transferring food liquids and conveying alcoholic beverages up to 50% alcohol content at 40°C.

#### CONNECTORS

Guillemin or Storz symmetrical connectors, cam or universal joint

connectors.

Fixings with band collars, single-thread or spiral collars (SERFLEX).

#### CHEMICAL RESISTANCE

See table column A.

#### WARNING

Spiral hoses have in general an elongation under pressure that can be important when temperature is above 40°C. This has to be considered before installation. We remain at your disposal for any question on this issue.

mm	± mm	mm	g/m	Bar	Bar	mm	Red spiral		Yellow spiral		Colorless spiral
							25 m	50 m	25 m	50 m	25 m
40	+/- 0,6	4,3	699	21	7	900	148939	148942	148940		148941
50	+/- 0,6	4,7	1020	21	7	900	148955	148968		148969	148957
60	+/- 0,6	4,8	1215	18	6	900	148971				
63	+/- 0,6	5,3	1351	18	6	900	148997				148999
70	+/- 0,6	5,5	1603	18	6	900	149013				149015
80	+/- 1	5,7	1798	15	5	900	149039				
100	+/- 1	7,0	2622	15	5	900	149042				
120	+/- 1	8,2	3496	15	5	800	149055				