


Suction and delivery ~ Special duty



SPIRABEL® BALNEO/PISCINE

+60
°C
-15

Hose reinforced with a rigid spiral
in a white soft PVC wall.



- 1 White spiral in rigid PVC
- 2 Wall in soft and white PVC.
Inner and outer smooth

Warning :
designation by the outside diameter

Marking : SPIRABEL BALNEO Ø out  [batch number]

APPLICATIONS

Swimming-pools and spas

ADVANTAGES

The manufacturing process designed to make Spirabel Balneo assures smooth inner and outer walls and a high precision of the outer diameter. This brings a total compatibility with plastic connectors used for swimming-pools or spas.
This hose is highly resistant to crushing and vacuum.

CONNECTORS




Usual plastic connectors for swimming-pool building.

CHEMICAL RESISTANCE

See table column A.

WARNING

Spiral hoses have in general an elongation under pressure that can be important when temperature is above 40°C. This has to be considered before installation. We remain at your disposal for any question on this issue.

∅ mm	± mm	g/m				White	
						25 m	50 m
32	+/- 0,4	346	21	7	80	168729	
40	+/- 0,4	513	19	6	120	168745	
50	+/- 0,4	633	18	6	190	168774	168780
63	+/- 0,4	943	15	5	250	168793	