


B.P.
60 bar

GPL ISO 3821 (EN 559)

+70
°C
-30

EN 559 - 2 Mpa (20 BAR) - 6 MM -  - 03

Flexible rubber hose for LPG



- 1 Cover in orange soft NBR/EPDM
- 2 Textile reinforcement
- 3 Inner tube in black soft NBR

Marking : NF EN 559 - ISO 3821 - PROPANE - 2 MPa (20 BAR) - Ø inn - [year of production]*

APPLICATIONS

- LPG (butane, propane...)
- Gas welding

SECTORS OF ACTIVITY

- Industry
- Building
- Shipyards










ADVANTAGES

This hose complies with ISO 3821 standard. It is very flexible (even at low temperature) and has a very good resistance to abrasion giving a longer service life. It can be used in any climatic conditions.

CONNECTORS

Usual connections for gas welding. Worm drive or 'O' type ring clamps. Crimping is possible with non damaging connectors.

* Year of production written in the marking is not a date of substitution

 mm	 mm	 mm	 mm	 mm	 g/m	 mm	 Bar	 mm	Orange 20 m
8	+/- 0,5	15	+/- 0,7	3,5	220	60	20	130	168426
10	+/- 0,5	17	+/- 0,8	3,5	265	60	20	150	168442